


WAAS CH 65842 W05A	APP CRS 047°	Rwy Idg TDZE Apt Elev	3800 411 422
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 5
DANIEL FLD (DNL)

RNP APCH. T A Baro-VNAV and VDP NA when using Augusta Rgnl at Bush Fld altimeter setting. Rwy 5 helicopter visibility reduction below ¾ SM NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C. When local altimeter not received use Augusta Rgnl at Bush Fld altimeter setting: Increase LPV DA to 716 feet, LNAV/VNAV DA to 1496 feet and all MDA 60 feet; Increase LPV all Cats visibility ½ SM, LNAV Cat A and Circling Cat C visibility ¼ SM.	MISSED APPROACH: Climb to 3400 direct FAMGO and hold, continue climb-in-hold to 3400.
---	---

ASOS 135.275	AUGUSTA APP CON ★ 126.8 270.3	UNICOM 123.05 (CTAF) 1
------------------------	---	----------------------------------



VGSJ and RNAV glidepath not coincident (VGSJ Angle 3.00°/TCH 30).				
GP 3.00° TCH 50				
TASPE				
CABOM				
RW05				
3400 FAMGO				
*LNAV only.				
*2.7 NM to RW05				
6 NM 2.2 NM 2.7 NM				
CATEGORY	A	B	C	D
LPV DA	661-¾ 250 (300-¾)			
LNAV/VNAV DA	1441-4 1030 (1100-4)			
LNAV MDA	1280-1 869 (900-1)	1280-1¼ 869 (900-1¼)	1280-2½ 869 (900-2½)	
CIRCLING	1280-1¼ 858 (900-1¼)		1360-2¾ 938 (1000-2¾)	1360-3 938 (1000-3)