

LOC I-FSD	APP CRS	Rwy Idg	8999
109.9	030°	TDZE	1424
		Apt Elev	1430

ILS or LOC RWY 3

JOE FOSS FLD (FSD)

T

A

ASR

-31°C

MALSR

MISSED APPROACH: Climb to 3400 then left turn direct FSD VORTAC and hold.

ATIS	SIoux FALLS APP CON *	SIoux FALLS TOWER *	GND CON	UNICOM
126.6	125.8 306.2	118.3 (CTAF) 0 257.8	121.9 348.6	122.95

ADF or RADAR REQUIRED

ALTERNATE MISSED APCH FIX

MSA FS 25 NM

One Minute Holding Pattern		FS LOM RADAR	3400	FSD	ELEV 1430	TDZE 1424
					REIL Rwy 15 and 33	1
GS 300° TCH 54		MAREY INT	*1940	*LOC only	HIRL Rwy 3-21 and 15-33	1
3400 ← 210° 030° → 3400		4.3 NM	1.4 NM		MIRL Rwy 9-27	1
CATEGORY	A	B	C	D	TDZ/CL Rwy 21	1
S-ILS 3	1674/24 250 (300-½)					1
S-LOC 3	1940/24	516 (600-½)	1940/55	516 (600-1)		1
CIRCLING	1960-1 530 (600-1)	1980-1 550 (600-1)	2060-1¾ 630 (700-1¾)	2200-2½ 770 (800-2½)		1
MAREY FIX MINIMUMS (DUAL VOR RECEIVERS REQUIRED)						1
S-LOC 3	1800/24	376 (400-½)	1800/35	376 (400-¾)		1
CIRCLING	1960-1 530 (600-1)	1980-1 550 (600-1)	2060-1¾ 630 (700-1¾)	2200-2½ 770 (800-2½)		1
FAF to MAP 5.7 NM						1
Knots		60	90	120	150	180
Min:Sec		5:42	3:48	2:51	2:17	1:54

SIoux FALLS, SOUTH DAKOTA

Amdt 27G 18JUN20

43°35'N-96°45'W

JOE FOSS FLD (FSD)

ILS or LOC RWY 3