

|                                        |                        |                                                   |                                         |
|----------------------------------------|------------------------|---------------------------------------------------|-----------------------------------------|
| WAAS<br>CH <b>63199</b><br><b>W17A</b> | APP CRS<br><b>174°</b> | Rwy Idg<br>TDZE <b>843</b><br>Apt Elev <b>845</b> | <b>7351</b><br><b>843</b><br><b>845</b> |
|----------------------------------------|------------------------|---------------------------------------------------|-----------------------------------------|

RNAV (GPS) RWY 17R

GRAND FORKS INTL (GFK)

RNP APCH - GPS.

▼

Baro-VNAV NA when using Crookston altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -20°C or above 54°C. VDP NA with Crookston altimeter setting.

⚠

When local altimeter setting not received, use Crookston altimeter setting and increase all DA 62 feet and all MDA 80 feet and increase LPV and LNAV/VNAV all Cats visibility  $\frac{1}{8}$  SM, LNAV Cats C/D visibility  $\frac{1}{8}$  SM, and Circling Cat C visibility  $\frac{1}{4}$  SM.

MISSED APPROACH:  
Climb to 2600 direct ERIXE and hold.

|                      |                                            |                                                   |                           |                            |                         |
|----------------------|--------------------------------------------|---------------------------------------------------|---------------------------|----------------------------|-------------------------|
| ATIS<br><b>119.4</b> | GRAND FORKS APP CON*<br><b>118.1 318.1</b> | GRAND FORKS TOWER*<br><b>118.4(CTAF) 0 350.35</b> | GND CON<br><b>124.575</b> | CLNC DEL<br><b>135.725</b> | UNICOM<br><b>122.95</b> |
|----------------------|--------------------------------------------|---------------------------------------------------|---------------------------|----------------------------|-------------------------|

