

WAAS CH 61100 W13A	APP CRS 131°	Rwy Idg TDZE Apt Elev	9200 358 366
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 13

EAST TEXAS RGNL (GGG)

RNP APCH.

⚠

Baro-VNAV NA when using Gilmer altimeter setting. VDP NA when using Gilmer altimeter setting. For inop ALS, increase LPV Cat E visibility to RVR 4000, LNAV/VNAV all Cats visibility to RVR 5500, LNAV Cat A/B visibility to RVR 5500, and LNAV Cat D/E visibility to 1¼ SM. When local altimeter setting not received use Gilmer altimeter setting and increase LPV DA to 671 feet; increase LNAV/VNAV DA to 785 feet, and visibility to RVR 4500; increase all MDA 60 feet, and LNAV Cats C/D visibility to RVR 5000, and Circling Cats C/D/E visibility ¼ SM. For inop ALS when using Gilmer altimeter setting, increase LPV all Cats visibility to RVR 4500, LNAV/VNAV Cat E visibility to 1¼ SM, and LNAV Cats A/B visibility to 5500, and LNAV Cats C/D/E visibility to 1½ SM. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C.

MALSR

MISSED APPROACH:
Climb to 3000 direct
FANAL and hold.

ATIS 119.65	LONGVIEW APP CON★ 124.675 257.975	EASTEX TOWER★ 119.2 (CTAF) 1377.05	GND CON 121.6	UNICOM 122.95
-----------------------	---	--	-------------------------	-------------------------

ELEV 366	D	TDZE 358
----------	----------	----------

4 NM Holding Pattern		BOSME		* LNAV only		3000	FANAL
6000 2600		311° 131°		131°		2300	
GP 3.00° TCH 42				WALT 2300		TOKUY 2.5 NM to RW13	
				* 1200		* 1.2 NM to RW13	
				6.3 NM		3.4 NM	
				1.3		1.2 NM	
CATEGORY	A	B	C	D	E		
LPV DA	612/24 254 (300-½)						
LNAV/VNAV DA	726/40 368 (400-¾)						
LNAV MDA	780/24	422 (500-½)	780/40 422 (500-¾)	780/50	422 (500-1)		
CIRCLING	860-1	494 (500-1)	980-1¾ 614 (700-1¾)	1080-2¼ 714 (800-2¼)	1080-2½ 714 (800-2½)		

LONGVIEW, TEXAS
Amdt 1C 22APR21

32°23'N-94°43'W

EAST TEXAS RGNL (GGG)

RNAV (GPS) RWY 13

SC-2, 22 FEB 2024 to 21 MAR 2024

SC-2, 22 FEB 2024 to 21 MAR 2024