

WAAS

CH **70526**

**W05A**

APP CRS

**054°**

Rwy Idg

**5502**

TDZE

**455**

Apt Elev

**459**

RNAV (GPS) RWY 5

MOORE COUNTY (SOP)

▼

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. For inop MALSR, increase LNAV/VNAV all Cats visibility to ¾ mile, LNAV Cats A/B visibility to 1 mile and LNAV Cats C/D visibility to 1½ mile. When local altimeter setting not received, use Sanford altimeter setting and increase all DA 88 feet and all MDA 100 feet, increase LNAV/VNAV all Cats visibility ½ mile, LNAV Cats C/D visibility ¾ mile, and Circling Cat C ½ mile. When using Sanford altimeter setting, for inop MALSR increase LNAV/VNAV all Cats visibility to 1½ mile, LNAV Cats A/B visibility to 1 mile, and LNAV Cat C/D visibility to 1¾ mile. Baro-VNAV and VDP NA when using Sanford altimeter setting.

MALSR

AS

MISSED APPROACH:

Climb to 2500 direct OWWEN and hold.

|                            |                                              |                          |                                  |
|----------------------------|----------------------------------------------|--------------------------|----------------------------------|
| AWOS-3PT<br><b>127.575</b> | FAYETTEVILLE APP CON<br><b>127.8 343.725</b> | CLNC DEL<br><b>127.0</b> | UNICOM<br><b>123.05 (CTAF) 0</b> |
|----------------------------|----------------------------------------------|--------------------------|----------------------------------|

Δ1048  
 30 NM to HEBNO  
 144°  
 2500  
 HEBNO  
 324°  
 2500  
 HEBNO (NoPT)  
 30 NM to HEBNO  
 144°  
 324°  
 2500  
 (IF/IAF) HEBNO  
 054°  
 234°  
 4 NM  
 Δ875  
 513  
 618±  
 WORBU  
 2 NM to RW05  
 (FAF) ZIKDA  
 609±  
 Δ994  
 934  
 2500  
 054°  
 234°  
 4 NM  
 R-5311 A, B, C  
 MISSED APCH FIX  
 4 NM  
 054°  
 234°  
 OWWEN

ELEV 459

D

TDZE 455

4 NM Holding Pattern

HEBNO

2500

←234°

→054°

2500

054°

2500

GP 3.00°

TCH 39

ZIKDA

2500

6 NM

4.3 NM

0.9 NM

1.1 NM

WORBU

2 NM to RW05

\*1120

1.1 NM to RW05

RW05

2500

OWWEN

\*LNAV only

| CATEGORY     | A                    | B                    | C                       | D                      |
|--------------|----------------------|----------------------|-------------------------|------------------------|
| LPV DA       | 655-½                |                      | 200 (200-½)             |                        |
| LNAV/VNAV DA | 750-½                |                      | 295 (300-½)             |                        |
| LNAV MDA     | 860-½ 405 (500-½)    |                      | 860-¾ 405 (500-¾)       |                        |
| CIRCLING     | 880-1<br>421 (500-1) | 920-1<br>461 (500-1) | 1100-1¾<br>641 (700-1¾) | 1360-3<br>901 (1000-3) |

REIL Rwy 23 0

HIRL Rwy 5-23 0

PINEHURST/SOUTHERN PINES, NORTH CAROLINA  
 Amdt 1A 22JUN17

35°14'N-79°23'W

MOORE COUNTY (SOP)  
**RNAV (GPS) RWY 5**